



technical data

Dimensions (WxDxH)	465 x 590 x 150 mm
Weight (incl. accessories/packaging)	Approx. 11.5 kg
Casing material	Galvanised steel
duct connection	BORA Ecotube
Filter material	Granular activated charcoal
Activated charcoal granulate volume	8.5 kg
Maximum filter service life	400 h (2 years)

Product description

- Service life approx. 400 h/2 years
- Combination of activated charcoal filter cartridges and upstream fine filter
- effective odour removal
- Complete BORA system

Scope of delivery

- Air cleaning box ULB3
- 3 x activated charcoal filter cartridges
- fine filter
- Housing plinth
- Fixing screw set
- 2 x angle brackets
- 2 x mounting straps
- operating and installation instructions

Accessories

- ULBAS replacement activated charcoal filter set

product- and planning instructions

- Diverse installation options
- Duct connection shallow 245 x 89 mm
- Access for maintenance must be considered during planning
- A shallow duct connector EFV is needed to form a direct link between the air cleaning box and the shallow duct
- Clearance of at least 2 cm is required to replace the filter cartridges
- Clearance of at least 18 cm is required sideways to replace the filter
- Ensure minimum return flow aperture of 500 cm² (e.g. shortened plinth plate or slatted plinth)